

VTU-KB06A-D

Android Network Control Keyboard



VTU-KB06A-D-F: with extension mini keypad module



VTU-KB06A-D: only host, without extension mini keypad module

Features:

- Touchscreen keyboard with the Android system.
- 10.1-inch capacitive touch screen, support local screen preview
- Four dimensional joystick control of PTZ functions
- Support H.265, H.264 codes decoding, max 1ch 4K@30 or 4ch 1080P@30
- Compatible with Viziontech cameras, storage devices, display control devices, and works with VTU-VMS
- Support snapshot and recording to U-disk
- Support video-wall display control and schemes switches
- The buttons on the keyboard can be used to perform operations such as zoom, focus and tour, and can use the iris, wiper and presets.
- VTU-KB06A-D-F model includes an extension keypad module (F1 cannot be called in platform TV wall mode)

Technical Specification

Model

Model	VTU-KB06A-D-(F)
-------	-----------------

System

Main Processor	Embedded Processor
----------------	--------------------

Operation System	ANDROID 7.1
------------------	-------------

Display

Video Output	1-ch VGA or 1-ch HDMI(extension decoding display 720P resolution)
--------------	---

Stream Type	H.265, H.264
-------------	--------------

Decoding Capability	1CH@4K(30fps)/4CH@1080P(30fps)/9CH@720P(30fps)
---------------------	--

Joystick	4D joystick
----------	-------------

Display split	1/4/9 splits, MxN splits
---------------	--------------------------

Screen	10.1" TFT LCD touch screen (1280*800)
--------	---------------------------------------

Audio & Alarm

Audio controller	1 × volume button, 1 × mute button and touchscreen control
------------------	--

Loudspeaker	1 loudspeaker to play audio
-------------	-----------------------------

Audio Input	1-ch 3.5 mm Jack
-------------	------------------

Audio Output	1-ch 3.5 mm Jack
--------------	------------------

General

Network Interface	1×RJ-45 port (10/100/1000M), WLAN
-------------------	-----------------------------------

USB Interface	1 USB3.0, 2 USB2.0
---------------	--------------------

WLAN	Support 2.4GHz (150Mbps transmission rate)
------	--

RS485	1 for ptz control
-------	-------------------

Maximum Number of Users	32 (including "admin")
-------------------------	------------------------

Max RS485 Addresses (Each User)	8
---------------------------------	---

Max Number of PTZ (IPC) That Can Be Added over Network (Each User)	1000
--	------

Environmental

Power Supply	12 VAC 4A max adapter, POE
--------------	----------------------------

Power Consumption	< 48 W
-------------------	--------

Working Temperature	-10°C ~+55°C
---------------------	--------------

Working Humidity	10%~95%
------------------	---------

Dimension	Host: 425mmx194mmx59mm (WxDxH) (exclude joystick) Mini Keypad: 421mmx105mmx26mm (WxDxH)
-----------	--

Gross weight	3.85kg(VTU-KB06A exclude package) 4.22kg(VTU-KB06A-D-F exclude package)
--------------	--

Net weight	1.90kg(VTU-KB06A exclude package) 2.36kg(VTU-KB06A-D exclude package)
------------	--

Dimensions(mm)

